









SPECIFICATIONS

TUBE COMPOSITION - POSTS. RAILS & PICKETS

ZAM™ Coated Cold Formed ERW Tubing

- With a coating designation **ZM 275** being a minimum protective coating weight of 275gm/m² both interior and exterior
- Top coat consisting of a chromium-free phosphate conversion coating
 Coating conforming to ASTM A1046 for hot dip coatings comprising of Zinc, Aluminum and Magnesium
- ERW tube conforming to ASTM A787 Type 6
 Minimum Yield Strength 207 MPa and Minimum Tensile Strength 290 MPa
 Weld seams mill re-metalized

MATERIAL DIMENSIONS		
PICKETS	5/8" × 5/8" (16mm × 16mm) 18 GA	
RAILS	1-1/4" × 1-1/4" (32mm × 32mm) 16 GA	
POSTS	2" × 2" (51mm × 51mm) 14 GA	
OPTIONAL POSTS(1)	2" × 2" (51mm × 51mm) 11 GA	
OPTIONAL POSTS(2)	2-1/2" × 2-1/2" (64mm × 64mm) 14 GA	

WELDS	Stainless Steel Mig Weld	
FITTINGS	14 Gauge Stamp Forged Finish as below	
FITTING FASTENERS	JS1000 Plated Finish as below	
OPTIONAL FASTENER	Tamper Proof Nuts	

FINISH		
GRADE	Super Durable Polyester Powder Coat	
OPTIONAL PRIMER	Zinc Rich Epoxy Powder Coat	
STANDARD COLOUR	Gloss Black	
OTHER COLOURS	Green, Brown, White, Antique Silver	
CUSTOM COLOURS	Per Specifications	

STANDARD	48"	60"	72"
HEIGHTS	1219mm	1524mm	1892mm

STANDARD GATES	Passage, Double Entry, Canatilever
----------------	------------------------------------



MEDALLION FENCE LTD

10651 KEELE STREET MAPLE, ONTARIO L6A 3Y9 (T) 905-832-2922 || 1-800-794-1564 || (F) 905-832-1564 info@medallionfence.com || www.medallionfence.com

MATERIAL SPECIFICATIONS: ARMOUR-SHIELD™ BY MEDALLION FENCE STYLE:

WINDSOR

SERIES:

4000

DATE: MM/DD/YYYY 1/15/2016