







TUBE COMPOSITION - POSTS. RAILS & PICKETS

Coated Cold Formed ERW Tubing

- A minimum protective coating weight of 275gm/m² both interior and exterior Top coat consisting of a chromium-free phosphate conversion coating
- Coating conforming to ASTM A1046 for hot dip coatings comprising of Zinc,
 Aluminum and Magnesium
 ERW tube conforming to ASTM A787 Type 6
 Minimum Yield Strength 207 MPa and Minimum Tensile Strength 290 MPa

- Weld seams mill re-metalized

MATERIAL DIMENSIONS		
PICKETS	5/8" × 5/8" (16mm × 16mm) 18 GA	
RAILS	1-1/4" × 1-1/4" (32mm × 32mm) 16 GA	
POSTS	2" × 2" (51mm × 51mm) 14 GA	
OPTIONAL POSTS(1)	2" × 2" (51mm × 51mm) 11 GA	
OPTIONAL POSTS(2)	2-1/2" × 2-1/2" (64mm × 64mm) 14 GA	

WELDS	Stainless Steel Mig Weld
FITTINGS	14 Gauge Stamp Forged Finish as below

OPTIONAL FASTENER	Tamper Proof Nuts
FITTING FASTENERS	JS1000 Plated Finish as below
FITTINGS	14 Gauge Stamp Forged Finish as below

GRADE	Super Durable Polyester Powder Coat
OPTIONAL PRIMER	Zinc Rich Epoxy Powder Coat
STANDARD COLOUR	Gloss Black
OTHER COLOURS	Green, Brown, White, Antique Silver
CUSTOM COLOURS	Per Specifications

STANDARD	36"	42"	48"	60"	72"
HEIGHTS	914mm	1067mm	1219mm	1524mm	1892mm

	1	
STANDARD GATES	Passage, Double Entry, Canatilever	



MEDALLION FENCE

10651 KEELE STREET

MAPLE, ONTARIO L6A 3Y9

(T) 905-832-2922 || 1-800-794-1564 || (F) 905-832-1564 info@medallionfence.com || www.medallionfence.com

MATERIAL SPECIFICATIONS:

ARMOUR-SHIELD™ BY MEDALLION FENCE

STYLE:

ALDEN

SERIES:

FAIRMONT™

DATE: MM/DD/YYYY

5/16/2025