









TUBE COMPOSITION - POSTS. RAILS & PICKETS

Coated Cold Formed ERW Tubing

- With a coating designation being a minimum protective coating weight of 275gm/m² both interior and exterior
 Top coat consisting of a chromium-free phosphate conversion coating
 Coating conforming to ASTM A1046 for hot dip coatings comprising of Zinc, Aluminum and Magnesium

- ERW tube conforming to ASTM A787 Type 6
 Minimum Yield Strength 207 MPa and Minimum Tensile Strength 290 MPa Weld seams mill re-metalized

MATERIAL DIMENSIONS			
PICKETS	5/8" × 5/8" (16mm × 16mm) 18 GA		
RAILS	1-1/4" × 1-1/4" (32mm × 32mm) 16 GA		
POSTS	2" × 2" (51mm × 51mm) 14 GA		
OPTIONAL POSTS(1)	2" × 2" (51mm × 51mm) 11 GA		
OPTIONAL POSTS(2)	2-1/2" × 2-1/2" (64mm × 64mm) 14 GA		

	0	
FITTINGS	14 Gauge Stamp Forged F	inish as below

Stainless Steel Mig Weld

FITTING FASTENERS JS1000 Plated Finish as below **OPTIONAL FASTENER** Tamper Proof Nuts

GRADE	Super Durable Polyester Powder Coat		
OPTIONAL PRIMER	Zinc Rich Epoxy Powder Coat		
STANDARD COLOUR	Gloss Black		
OTHER COLOURS	Green, Brown, White, Antique Silver		
CUSTOM COLOURS	Per Specifications		

STANDARD	48"	60"	72"
HEIGHTS	1219mm	1524mm	1892mm

STANDARD GATES Passage, Double Entry, Canatilever



MEDALLION FENCE

10651 KFFLF STRFFT

MAPLE, ONTARIO L6A 3Y9

(T) 905-832-2922 || 1-800-794-1564 || (F) 905-832-1564 info@medallionfence.com || www.medallionfence.com

MATERIAL SPECIFICATIONS:

ARMOUR-SHIELD™ BY MEDALLION FENCE

STYLE:

ARISTOCRAT

WELDS

SERIES:

FAIRMONT™

DATE: MM/DD/YYYY

5/16/2025