

OPTIONAL CAST FINIAL



Fleur Des Lis (FF)

OPTIONAL POST CAPS



Pyramid



Ball



Spiral

PROTECTED BY



ARMOUR-SHIELD™

SPECIFICATIONS

TUBE COMPOSITION - POSTS, RAILS & PICKETS

Coated Cold Formed ERW Tubing

- With a coating designation being a minimum protective coating weight of 275gm/m² both interior and exterior
 - Top coat consisting of a chromium-free phosphate conversion coating
 - Coating conforming to ASTM A1046 for hot dip coatings comprising of Zinc, Aluminum and Magnesium
 - ERW tube conforming to ASTM A787 Type 6
 - Minimum Yield Strength 207 MPa and Minimum Tensile Strength 290 MPa
- Weld seams mill re-metalized

MATERIAL DIMENSIONS

PICKETS	5/8" × 5/8" (16mm × 16mm) 18 GA
RAILS	1-1/4" × 1-1/4" (32mm × 32mm) 16 GA
POSTS	2" × 2" (51mm × 51mm) 14 GA
OPTIONAL POSTS(1)	2" × 2" (51mm × 51mm) 11 GA
OPTIONAL POSTS(2)	2-1/2" × 2-1/2" (64mm × 64mm) 14 GA

WELDS	Stainless Steel Mig Weld
-------	--------------------------

FITTINGS	14 Gauge Stamp Forged Finish as below
----------	---------------------------------------

FITTING FASTENERS	JS1000 Plated Finish as below
-------------------	-------------------------------

OPTIONAL FASTENER	Tamper Proof Nuts
-------------------	-------------------

GRADE	Super Durable Polyester Powder Coat
-------	-------------------------------------

OPTIONAL PRIMER	Zinc Rich Epoxy Powder Coat
-----------------	-----------------------------

STANDARD COLOUR	Gloss Black
-----------------	-------------

OTHER COLOURS	Green, Brown, White, Antique Silver
---------------	-------------------------------------

CUSTOM COLOURS	Per Specifications
----------------	--------------------

STANDARD HEIGHTS	51" 1295mm	63" 1600mm	75" 1905mm
------------------	---------------	---------------	---------------

STANDARD GATES	Passage, Double Entry, Canatilever
----------------	------------------------------------

Post Setting 94" [2388mm] (Inside Posts)

92" [2337mm] (Standard Panel Width)

2 3/8" [60mm]

3 1/2" [89mm]
(Between Pickets)

7-1/4" [184mm]

3 1/2" [89mm]

56-1/4" [1429mm] for 75" fence
44-1/4" [1124mm] for 63" fence
32-1/4" [819mm] for 51" fence

4" [102mm]

Precision Punched Solid Tube
For Picket Insertion



MEDALLION FENCE

10651 KEELE STREET
MAPLE, ONTARIO L6A 3Y9

(T) 905-832-2922 || 1-800-794-1564 || (F) 905-832-1564
info@medallionfence.com || www.medallionfence.com

MATERIAL SPECIFICATIONS:

ARMOUR-SHIELD™ BY MEDALLION FENCE

STYLE:

CAVALIER SF-DR

SERIES:

FAIRMONT™

DATE: MM/DD/YYYY

5/16/2025