



OPTIONAL CAST FINIAL



Fleur Des Lis (FF)

OPTIONAL POST CAPS



Pyramid



Ball



Spiral

SPECIFICATIONS

TUBE COMPOSITION - POSTS, RAILS & PICKETS

Marine Grade Aluminum

• 6061-T6

MATERIAL DIMENSIONS

PICKETS	5/8" × 5/8" (16mm × 16mm) .080 Wall
RAILS	1-1/4" × 1-1/4" (32mm × 32mm) .102 Wall
POSTS	2" × 2" (51mm × 51mm) .125 Wall
OPTIONAL POSTS	2-1/2" × 2-1/2" (64mm × 64mm) .125 Wall

WELDS	Aluminum Mig Weld
-------	-------------------

FITTINGS	14 Gauge Stamp Forged Finish as below
----------	---------------------------------------

FITTING FASTENERS	JS1000 Plated Finish as below
-------------------	-------------------------------

OPTIONAL FASTENER	Tamper Proof Nuts
-------------------	-------------------

FINISH

GRADE	Super Durable Polyester Powder Coat
OPTIONAL PRIMER	Zinc Rich Epoxy Powder Coat
OPTIONAL PRIMER(2)	E-Coat
STANDARD COLOUR	Gloss Black
OTHER COLOURS	Green, Brown, White, Antique Silver
CUSTOM COLOURS	Per Specifications

STANDARD HEIGHTS	48" 1219mm	60" 1524mm	72" 1892mm
------------------	---------------	---------------	---------------

STANDARD GATES	Passage, Double Entry, Canatilever
----------------	------------------------------------

Post Setting 94" [2388mm] (Inside Posts)

92" [2337mm] (Standard Panel Width)

2 3/8" [60mm]

3 1/2" [89mm]
(Between Pickets)

4-1/2" [114mm]

60" (1524mm) for 72" fence
48" (1219mm) for 60" fence
36" (914mm) for 48" fence

4" [102mm]

Percision Punched Solid Tube
For Picket Insertion

MEDALLION FENCE

10651 KEELE STREET

MAPLE, ONTARIO L6A 3Y9

(T) 905-832-2922 || 1-800-794-1564 || (F) 905-832-1564

info@medallionfence.com || www.medallionfence.com

MATERIAL SPECIFICATIONS:

Alu-Tuff™ BY MEDALLION FENCE

STYLE:

REGAL-AL

SERIES:

FAIRMONT™

DATE: MM/DD/YYYY

5/16/2025