







TUBE COMPOSITION - POSTS, RAILS & PICKETS

Coated Cold Formed ERW Tubing

- With a coating designation ZM 275 being a minimum protective coating weight of 275gm/m² both interior and exterior
- Top coat consisting of a chromium-free phosphate conversion coating
 Coating conforming to ASTM A1046 for hot dip coatings comprising of Zinc, Aluminum and Magnesium
- ERW tube conforming to ASTM A787 Type 6
 Minimum Yield Strength 207 MPa and Minimum Tensile Strength 290 MPa Weld seams mill re-metalized

MATERIAL DIMENSIONS				
PICKETS	5/8" × 5/8" (16mm × 16mm) 18 GA			
RAILS	1-1/4" × 1-1/4" (32mm × 32mm) 16 GA			
POSTS	2" × 2" (51mm × 51mm) 14 GA			
OPTIONAL POSTS(1)	2" × 2" (51mm × 51mm) 11 GA			
OPTIONAL POSTS(2)	2-1/2" × 2-1/2" (64mm × 64mm) 14 GA			

WELDS	Stainless Steel Mig Weld	

FITTINGS	14 Gauge Stamp Forged Finish as below			
FITTING FASTENERS	JS1000 Plated Finish as below			
OPTIONAL FASTENER	Tamper Proof Nuts			

GRADE	Super Durable Polyester Powder Coat
OPTIONAL PRIMER	Zinc Rich Epoxy Powder Coat
STANDARD COLOUR	Gloss Black
OTHER COLOURS	Green, Brown, White, Antique Silver
CUSTOM COLOURS	Per Specifications

STANDARD	36"	42"	48"	60"	72"
HEIGHTS	914mm	1067mm	1219mm	1524mm	1892mm

STANDARD GATES Passage, Double Entry, Canatilever



MEDALLION FENCE

10651 KEELE STREET

MAPLE, ONTARIO L6A 3Y9

(T) 905-832-2922 || 1-800-794-1564 || (F) 905-832-1564 info@medallionfence.com || www.medallionfence.com

MATERIAL SPECIFICATIONS:

ARMOUR-SHIELD™ BY MEDALLION FENCE

STYLE:

STANTON

SERIES:

FAIRMONT™

DATE: MM/DD/YYYY

5/16/2025